

**ILSCO**<sup>®</sup>

connections  
matter

**INSPECTABLE  
Pre-Insulated  
Mechanical  
Connectors**

# CLEAR TAP<sup>®</sup>

**Performance**

**Versatility**

**Simplicity**



1.800.776.9775

sales@ilsco.com

www.ilsco.com

**Single- and Dual-Sided Entry Insulated Multi-Tap Connectors,  
and Two Wire In-line and Offset Insulated Splicer-Reducers  
with a Broad Wire Range of 750 kcmil to 14 AWG**

# More Wire Combinations. Less Hassle. More Versatility. Less Parts to Inventory. And That's Good for Your Bottom Line.

ClearTap® insulated multi-tap connectors are now available in single and dual side entry as well as two wire in-line and offset configurations. ClearTap is UL Listed, CSA Certified, range-taking, and dual-rated for Class B & C copper and Class B aluminum conductors. Every conductor port is pre-filled with ILSCO De-Ox® oxide inhibitor for high reliability and resistance to corrosion. With a conductor range of 750kcmil – 14 the connectors are fully insulated with a transparent cover, eliminating the need for tape and allowing for easy visual inspection to ensure a safe and reliable connection.



ECTS



ECTD

ClearTap® Single- and Dual-Sided Entry Insulated Multi-Tap Connectors




ECT



ECTO

ClearTap® Two Wire In-line and Offset Insulated Splicer-Reducers



Dual-sided entry application



Conductor insertion and oxide inhibitor presence can be visually verified after installation.

