



**Recommended Tightening Torque Values for
UTILCO Dual Rated Socket Screw Connectors**

Wire Range AL or CU	Torque	
	in-lbs	ft-lbs
#14 AWG to #3 AWG	120	10
#2 AWG to 350 kcmil	240	20
400 kcmil to 750 kcmil	360	30
800 kcmil to 1000 kcmil	480	40

For transformer stud-mounted connectors, slip connector fully onto stud. Tighten the stud mounting set screws to 180 - 220 in-lbs to lock connector to stud.

FORM 18

6/3/2009



**Recommended Tightening Torque Values for
UTILCO Dual Rated Socket Screw Connectors**

Wire Range AL or CU	Torque	
	in-lbs	ft-lbs
#14 AWG to #3 AWG	120	10
#2 AWG to 350 kcmil	240	20
400 kcmil to 750 kcmil	360	30
800 kcmil to 1000 kcmil	480	40

For transformer stud-mounted connectors, slip connector fully onto stud. Tighten the stud mounting set screws to 180 - 220 in-lbs to lock connector to stud.

FORM 18

6/3/2009



**Recommended Tightening Torque Values for
UTILCO Dual Rated Socket Screw Connectors**

Wire Range AL or CU	Torque	
	in-lbs	ft-lbs
#14 AWG to #3 AWG	120	10
#2 AWG to 350 kcmil	240	20
400 kcmil to 750 kcmil	360	30
800 kcmil to 1000 kcmil	480	40

For transformer stud-mounted connectors, slip connector fully onto stud. Tighten the stud mounting set screws to 180 - 220 in-lbs to lock connector to stud.

FORM 18

6/3/2009



**Recommended Tightening Torque Values for
UTILCO Dual Rated Socket Screw Connectors**

Wire Range AL or CU	Torque	
	in-lbs	ft-lbs
#14 AWG to #3 AWG	120	10
#2 AWG to 350 kcmil	240	20
400 kcmil to 750 kcmil	360	30
800 kcmil to 1000 kcmil	480	40

For transformer stud-mounted connectors, slip connector fully onto stud. Tighten the stud mounting set screws to 180 - 220 in-lbs to lock connector to stud.

FORM 18

6/3/2009